LIME-BASED TEXTURED FINISH

Atmosfere

Ready to use

Mineral decorative coating in paste form, based on lime putty and marble powders. It can be used to create textured surfaces, satin finishes and effects such as Pietra Spaccata, Pietra Zen and stencil work, by varying the technique and tools.

Intended uses

- Interior decorative walls and panels.
- Pietra Spaccata, Pietra Zen and textured finishes.
- Decorative stencil work on compatible substrates.

Product data

Property	Value / instruction
Product type	Lime- and marble-powder-based mineral levelling paste
Preparation	Ready to use; stir until uniform without adding water
Maximum particle size	800 µm (0.8 mm)
Indicative consumption	Approximately 2 kg/m² for a finished surface; varies with the texture
Application	Stainless steel trowel and tools for the chosen decorative technique
Pack sizes	4 kg and 24 kg
Colour	White 300 and shades from the 300 colour chart
Application conditions	Temperature at least +5 °C; relative humidity no higher than 75%
Recommended interval	8 hours on a dry layer; see the application instructions for the build-up system

Antonio Liso · Via Sempione 27 · 20021 Baranzate (MI), Italy
www.decoriamonoi.it

Preparation and application

1. Substrate preparation

Brush and scrape away unsound material; check the adhesion of the plaster and existing paint. The substrate must be stable, clean and dry. Apply a compatible isolating primer when required by the substrate.

2. Stirring and application

Stir the paste without adding water. Apply with a stainless steel trowel, maintaining an even, flat coat. Shape the material with tools suitable for the chosen effect; thickness and technique affect consumption.

3. Traditional build-up system

For an initial coat approximately 2 mm thick, wait at least 24 hours before applying the lighter second coat. Smooth with a clean stainless steel trowel at the appropriate working stage, gradually increasing the pressure.

4. Completion and protection

For interior finishes, assess compatible waxes and glazes on a sample of the complete system. Outdoors, protect from rain for at least three days; apply any silicone-based protective treatment specified by the system after at least ten days.

Application notes

The recommended 8-hour interval applies to a layer that is already dry. The traditional system with a first coat approximately 2 mm thick requires at least 24 hours. Cold conditions, humidity and greater thickness extend the waiting time. Colours are indicative.

Storage

Protect from frost. Store in the tightly closed original packaging in suitable premises, away from direct sunlight. Shelf life: 12 months in the original packaging when correctly stored.

Safety

Alkaline product: pH above 12. Avoid contact with skin and eyes; wear gloves and protect the eyes and face. Consult the Safety Data Sheet and label for complete information on hazards, protection and disposal. Do not release the product into the environment.

Document reference

English translation of the Italian technical data sheet currently published at Decoriamonoi.it. Italian source: 01 / 16.11.2026. English edition: 01 / 18 November 2026. The technical values, stated test scope and application limitations of the Italian source are retained.

Technical enquiries: antonioliso@me.com · +39 349 344 2676 · www.antonioliso.com