GLOSS ACRYLIC DECORATIVE PLASTER

Plaster Glass

Ready to use

Acrylic decorative plaster in paste form for smooth, dense and lustrous interior wall finishes, with a glossy, glass-like appearance and marble-like tonal effects. Formulated with acrylic resins, selected fillers and specific additives.

Intended uses

- Interior walls in homes, showrooms, shops and commercial premises.
- Cured plaster, plasterboard and correctly prepared gypsum- or cement-based skim coats.
- Smooth, glossy decorative finishes with colour and marble effects.

Product data

Property	Value / instruction
Product type	Acrylic decorative plaster paste
Preparation	Ready to use
Application	Three coats with a stainless steel trowel
Indicative consumption	Approximately 1 kg/m² for the complete system
Recommended interval	8 hours between coats; check that the preceding layer is completely dry
Indicative drying times	Dust-dry: 2-3 hours; touch-dry: 6-8 hours; fully dry: approximately 24 hours
Pack sizes and colours	4 kg and 20 kg; White 300 and shades from the 300 colour chart
pH / density	pH 8.5; density 1.65 ± 0.10 g/cm³ at 20 °C

Antonio Liso · Via Sempione 27 · 20021 Baranzate (MI), Italy
www.decoriamonoi.it

Preparation and application

1. Substrate preparation

Ensure that the substrate is dry, clean, sound and even. On compatible plaster, plasterboard and skim coats, apply Fondo Primer Medio and allow it to dry before applying the decorative finish.

2. Material preparation

Stir the ready-to-use paste until uniform. Where needed for the chosen technique, dilution with a maximum of 5% water is permitted. Use clean tools and mix evenly.

3. Three-coat application

Apply even coats with a stainless steel trowel. Carefully control the passes and final working to obtain density, tonal variation and gloss. Between coats separated by drying, wait 8 hours and check the substrate.

4. Finish inspection

Prepare a complete sample of the colour and technique. The stated times are indicative and depend on the substrate, environment and thickness. Clean tools with water immediately after use.

Application notes

Colours are indicative: light, substrate and technique affect the perceived finish. The product is ready to use; the optional maximum 5% water is a workability adjustment, not mandatory dilution.

Storage

Store in a cool, dry place, in the intact, tightly closed original container, protected from frost and excessive heat. Shelf life: 12 months in unopened packaging.

Safety

Consult the label and Safety Data Sheet. The product contains preservatives that may cause an allergic reaction. Avoid contact with skin and eyes, use suitable protection and do not release residues into the environment.

Document reference

English translation of the Italian technical data sheet currently published at Decoriamonoi.it. Italian source: 01 / 16.11.2026. English edition: 01 / 18 November 2026. The technical values, stated test scope and application limitations of the Italian source are retained.

Technical enquiries: antonioliso@me.com · +39 349 344 2676 · www.antonioliso.com